





Technische specificatie nr. TS BG8-3 Uitgiftedatum: 07-01-2026	 23 0063-CPR-300081 DoP nr. BG8-260107	 1916-20-k
---	--	--

Betongranulaat 0/8

EN 12620:2002 + A1:2008
 Toeslagmateriaal voor beton

Zeef (mm)	16	11,2	8	5,6	4	2	1	0,500	0,250	0,125	0,063
Gem. doorval (%)	100	100	96	82	67	50	38	26	10	5	2,4
Min. Norm	100	98	85	-	50	-	20	-	-	-	0
Max. norm	-	100	99	-	90	-	60	-	-	-	11

Prestaties	
Korrelgroep	0/8
Gradering	G _A 85
Gehalte zeer fijn materiaal	f ₁₁
Kwaliteit fijn materiaal	MB <0,2
Korrel dichtheid (ρ _{rd})	2,24 ± 0,11 Mg/m ³
Waterabsorptie WA ₂₄	8,2 ± 2,6 %
Chloride	≤ 0,10 %
In zuur oplosbaar sulfaat	AS _{0,8}
Water oplosbare sulfaten van gerecycled toeslagmateriaal	SS _{0,2}
Bepaling humusgehalte	Negatief
Verandering van bindtijd van cement	A ₄₀
Gehalte asbest	< 100 mg/kg d.s.

Naam:	M. de Koning	Datum:	07-01-2026
Functie:	Kwaliteitscoördinator	Handtekening:	